

CyberFront SL-B

Owner's manual

T-Line

DESTINATION

Brompton folding bikes, 74mm fork width, T-Line models.

GUIDELINE

Never use high-pressure spray washing directly onto the hub.

Warning: Water and moisture stagnant inside hub can permanently damage bearings.

Clean hubs externally with warm water and soap.

WARNING:

- 1) **Micro-Tuner must be on left side of the bicycle.**
- 2) Incorrect bearing preload may seriously damage bearings/parts and decreases performance.



Keep original hook

INSTALLATION

CyberFront SL-B features the special B-Lock system to secure the wheel to the frame saving the weight of the Quick release. Left side B-Lock bolt pass through the fork and the original T-Line fork hook.

Tighten B-Lock left bolt at 6Nm and B-Lock front bolt at 10Nm.

Studio Riva SRL - Tel: ++39-0371-203059
info@extralite.com - www.extralite.com



BEARING SET-UP

Bearings come pre-adjusted from the factory. Optimal preload is important for long bearing life.

Preload checking

Before modifying bearing preload carefully check the complete wheel as follows:

- 1) Install the complete wheel into dropouts and normally tight B-Lock bolts at 10Nm
- 2) Check there is no play at rim diameter.
- 3) Leave wheel free to completely stop spinning and carefully control latest instants of movement. Stopping should be very smooth.

Preload tuning

If necessary fine tune as follows.

- 1) Hold right axle end with 5mm allen and gently turn Micro Tuner fully clockwise by hand or with a 17mm wrench.
- 2) Unscrew Micro Tuner for 1/8 to 1/4 of turn. You can snap out Left Axle End to enable operation.
- 3) Repeat preload checking and eventually slightly correct it. Turn anti-clockwise to increase rolling and stopping smoothness. Turn clockwise to correct play.

Wheelbuilder's manual

DIMENSION FOR WHEEL BUILDING:

Spoke hole Ø: 2.8mm
Flanges drilling Ø: 29mm
Center to flanges: 24mm

See www.extralite.com to find pre-calculated spoke lengths.

WARNINGS:

Never exceed maximum hub spoke tension: 90Kgf (radial)/ 110Kgf (crossed spokes)

Reduce tension if the rim manufacturer recommends a lower value.

To prevent galvanic corrosion do not install metal washers between spokes heads and flange.

Do not laterally over-push Axle at the spoke stretching procedure.

Extralite Limited Warranty

Extralite products are warranted against defects in materials and/or workmanship for a period of two years from original date of purchase to the original owner only. Any Extralite product that is returned and found by Studio Riva to be defective in materials and/or workmanship will be repaired or replaced at the sole discretion of Studio Riva. This warranty is the sole and exclusive remedy. Studio Riva shall not be held liable for any indirect, special or consequential damages. The warranty is expressly limited to repair or replacement of the product that has been returned and found to be defective by Studio Riva and are the sole remedy of the warranty. No credits or refunds will be issued. The warranty does not cover: normal wear, tear and fatigue; damage or failure due to accident or collision. Improper assembling, poor maintenance, alterations or modifications, installation of parts not compatible with Extralite products void this warranty. Warranty does not cover damage arising from crash, abuse and/or misuse or any other circumstances in which the product had been subjected to forces or loads beyond its design. Immediately replace the component after crash and violent shock, or after continuous heavy use. Improper use, modification and/or part changing, including surface finishing, could irreparably damage the component. All labor charges for warranty service are responsibility of the product owner.

INSTALLATION WARNING: Extralite components are extremely performing and lightweight, crafted with very high quality, they request adequate installation and maintenance care. We strongly recommended that a professional bike shop install and service your Extralite components. Improper assembly and/or adjustment may significantly compromise strength and durability of the component causing serious personal injury. Carefully check proper tightening torque of every bolt. Always respect installation recommendations. Extralite components are designed for a specific use X-Country or Road or Downhill, respect product specific destination. Note: the rider assumes all the risks regarding use and installation of Extralite components.